

## Product Ecodesign Information

Model No.: Weheat Blackbird P80

Air-to-water heat pump [YES/NO]:	YES	Low-temperature heat pump [YES/NO]:	NO
Water-to-water heat pump [YES/NO]:	NO	Brine-to-water heat pump [YES/NO]:	NO
Equipped with a supplementary heater [YES/NO]:	YES		
Heat pump combination heater [YES/NO]:	YES		

Parameters shall be declared for medium-temperature application.

Parameters shall be declared for AVERAGE climate conditions:-

Item	Symb.	Value	Unit	Item	Symb.	Value	Unit
Rated heat output (*)	P rated	8	kW	Seasonal space heating energy efficiency	$\eta_s$	184	%
Bivalent temperature	$T_{biv}$	-7	°C	Operation limit temperature	TOL	-10	°C
Degradation coefficient (**)	$C_{dh}$	0,99	—	Heating water operating limit temperature	WTOL	70	°C

Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature  $T_j$

Declared coefficient of performance for part load at indoor temperature 20 °C and outdoor temperature  $T_j$

$T_j = -7$ °C	$P_{dh}$	6,7	kW	$T_j = -7$ °C	$COP_d$	3,2	—
$T_j = +2$ °C	$P_{dh}$	4,4	kW	$T_j = +2$ °C	$COP_d$	4,5	—
$T_j = +7$ °C	$P_{dh}$	2,9	kW	$T_j = +7$ °C	$COP_d$	6,4	—
$T_j = +12$ °C	$P_{dh}$	3,4	kW	$T_j = +12$ °C	$COP_d$	8,4	—
$T_j = T_{biv}$	$P_{dh}$	—	kW	$T_j = T_{biv}$	$COP_d$	—	—
$T_j = TOL$	$P_{dh}$	—	kW	$T_j = TOL$	$COP_d$	—	—
$T_j = -10$ °C (if TOL < 20 °C)	$P_{dh}$	—	kW	$T_j = -10$ °C (if TOL < 20 °C)	$COP_d$	—	—
Cycling interval capacity for heating	$P_{cyc}$	—	kW	Cycling interval efficiency	$COP_{cyc}$	—	—

Power consumption in modes other than active mode:

Other items: (◊) (◻)

Off mode	$P_{OFF}$	0,000	kW	Capacity control	Variable		
Thermostat-off mode	$P_{TO}$	0,028	kW	Sound power level, indoor (◊)	$L_{WA}$	30	dB
Standby mode	$P_{SB}$	0,028	kW	Sound power level, outdoor (◊)	$L_{WA}$	65	dB
Crankcase heater mode	$P_{CK}$	0,000	kW	Sound power level, indoor (◻)	$L_{WA}$	30	dB
Supplementary heater	$P_{sup}$	3	kW	Sound power level, outdoor (◻)	$L_{WA}$	65	dB
Rated heat output (*)				Annual energy consumption	$Q_{HE}$	***	kWh
Type of energy input				Rated air flow rate outdoor			m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	—	—	m <sup>3</sup> /h	Emissions of nitrogen oxides	$NO_x$	—	mg/kWh

For heat pump combination heater:

Declared load profile	M			Water heating energy efficiency	$\eta_{wh}$	123,5	%
Daily electricity consumption	$Q_{elec}$	3	kWh	Daily fuel consumption	$Q_{fuel}$	—	kWh

Contact details for obtaining more information

(Name and address of the manufacturer or of its authorized representative.)  
Weheat B.V.  
Wolverstraat 23, 5525 AR Duizel, NL

REMARK:

- You can find information and precautions relevant for installation and maintenance in the Operation Instructions.
- You can find information relevant for recycling and/or disposal at end-of-life in the Operation Instructions.

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output  $P_{rated}$  is equal to the design load for heating  $P_{designh}$ , and the rated heat output of a supplementary heater  $P_{sup}$  is equal to the supplementary capacity for heating  $sup(T_j)$ .

(\*\*) If  $C_{dh}$  is not determined by measurement, then the default degradation coefficient is  $C_{dh} = 0,9$ .

(\*\*\*) See the attached Energy Performance Quality Declaration in accordance with NTA 8800:2024

(◊) Nominal A-Weighted Sound Power Level (LWA), according to regulation 811/2013, 813/2013 and standard EN14825 at A7(6), in dB (A).

(◻) Maximum A-Weighted Sound power level (LWA), according to EN12102-1 at A7(6) W55(47), in dB (A).