

Product Ecodesign Information

Model No.: Weheat Blackbird P80

Air-to-water heat pump [YES/NO]:	YES	Low-temperature heat pump [YES/NO]:	NO
Water-to-water heat pump [YES/NO]:	NO	Brine-to-water heat pump [YES/NO]:	NO
Equipped with a supplementary heater [YES/NO]:	YES		
Heat pump combination heater [YES/NO]:	YES		

Parameters shall be declared for medium-temperature application.

Parameters shall be declared for AVERAGE climate conditions:-

Item	Symb.	Value	Unit	Item	Symb.	Value	Unit
Rated heat output (*)	P rated	8	kW	Seasonal space heating energy efficiency	η_s	184	%
Bivalent temperature	T_{biv}	-7	°C	Operation limit temperature	TOL	-10	°C
Degradation coefficient (**)	C_{dh}	0,99	—	Heating water operating limit temperature	WTOL	70	°C

Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j

Declared coefficient of performance for part load at indoor temperature 20 °C and outdoor temperature T_j

$T_j = -7$ °C	P_{dh}	6,7	kW	$T_j = -7$ °C	COP_d	3,2	—
$T_j = +2$ °C	P_{dh}	4,4	kW	$T_j = +2$ °C	COP_d	4,5	—
$T_j = +7$ °C	P_{dh}	2,9	kW	$T_j = +7$ °C	COP_d	6,4	—
$T_j = +12$ °C	P_{dh}	3,4	kW	$T_j = +12$ °C	COP_d	8,4	—
$T_j = T_{biv}$	P_{dh}	—	kW	$T_j = T_{biv}$	COP_d	—	—
$T_j = TOL$	P_{dh}	—	kW	$T_j = TOL$	COP_d	—	—
$T_j = -10$ °C (if $TOL < 20$ °C)	P_{dh}	—	kW	$T_j = -10$ °C (if $TOL < 20$ °C)	COP_d	—	—
Cycling interval capacity for heating	P_{cyc}	—	kW	Cycling interval efficiency	COP_{cyc}	—	—

Power consumption in modes other than active mode:

Other items: (◊) (◻)

Off mode	P_{OFF}	0,000	kW	Capacity control	Variable		
Thermostat-off mode	P_{TO}	0,028	kW	Sound power level, indoor (◊)	L_{WA}	30	dB
Standby mode	P_{SB}	0,028	kW	Sound power level, outdoor (◊)	L_{WA}	65	dB
Crankcase heater mode	P_{CK}	0,000	kW	Sound power level, indoor (◻)	L_{WA}	30	dB
Supplementary heater	P_{sup}	3	kW	Sound power level, outdoor (◻)	L_{WA}	65	dB
Rated heat output (*)				Annual energy consumption	Q_{HE}	***	kWh
Type of energy input				Rated air flow rate outdoor			m ³ /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	—	—	m ³ /h	Emissions of nitrogen oxides	NO_x	—	mg/kWh

For heat pump combination heater:

Declared load profile	L			Water heating energy efficiency	η_{wh}	125,6	%
Daily electricity consumption	Q_{elec}	3	kWh	Daily fuel consumption	Q_{fuel}	—	kWh

Contact details for obtaining more information

(Name and address of the manufacturer or of its authorized representative.)
Weheat B.V.
Wolverstraat 23, 5525 AR Duizel, NL

REMARK:

- You can find information and precautions relevant for installation and maintenance in the Operation Instructions.
 - You can find information relevant for recycling and/or disposal at end-of-life in the Operation Instructions.
- (*) For heat pump space heaters and heat pump combination heaters, the rated heat output P_{rated} is equal to the design load for heating $P_{designh}$, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating $sup(T_j)$.
- (**) If C_{dh} is not determined by measurement, then the default degradation coefficient is $C_{dh} = 0,9$.
- (***) See the attached Energy Performance Quality Declaration in accordance with NTA 8800:2024
- (◊) Nominal A-Weighted Sound Power Level (LWA), according to regulation 811/2013, 813/2013 and standard EN14825 at A7(6), in dB (A).
- (◻) Maximum A-Weighted Sound power level (LWA), according to EN12102-1 at A7(6) W55(47), in dB (A).